

The P00Ltype processor

(Version 3, September 1989)

	Section	Page
Introduction	1	102
The character set	4	103
String handling	12	106
System-dependent changes	21	109
Index	22	110

The preparation of this report was supported in part by the National Science Foundation under grants IST-8201926 and MCS-8300984, and by the System Development Foundation. 'T_EX' is a trademark of the American Mathematical Society.

1. Introduction. The `POOLtype` utility program converts string pool files output by `TANGLE` into a slightly more symbolic format that may be useful when `TANGLED` programs are being debugged.

It's a pretty trivial routine, but people may want to try transporting this program before they get up enough courage to tackle `TEX` itself. The first 256 strings are treated as `TEX` treats them, using routines copied from `TEX82`.

2. `POOLtype` is written entirely in standard Pascal, except that it has to do some slightly system-dependent character code conversion on input and output. The input is read from *pool_file*, and the output is written on *output*. If the input is erroneous, the *output* file will describe the error.

```
program POOLtype(pool_file, output);
  label 9999; { this labels the end of the program }
  type <Types in the outer block 5>
  var <Globals in the outer block 7>
  procedure initialize; { this procedure gets things started properly }
    var <Local variables for initialization 6>
    begin <Set initial values of key variables 8>
    end;
```

3. Here are some macros for common programming idioms.

```
define incr(#) ≡ # ← # + 1 { increase a variable by unity }
define decr(#) ≡ # ← # - 1 { decrease a variable by unity }
define do_nothing ≡ { empty statement }
```

4. The character set. (The following material is copied verbatim from T_EX82. Thus, the same system-dependent changes should be made to both programs.)

In order to make T_EX readily portable to a wide variety of computers, all of its input text is converted to an internal eight-bit code that includes standard ASCII, the “American Standard Code for Information Interchange.” This conversion is done immediately when each character is read in. Conversely, characters are converted from ASCII to the user’s external representation just before they are output to a text file.

Such an internal code is relevant to users of T_EX primarily because it governs the positions of characters in the fonts. For example, the character ‘A’ has ASCII code 65 = ‘101’, and when T_EX typesets this letter it specifies character number 65 in the current font. If that font actually has ‘A’ in a different position, T_EX doesn’t know what the real position is; the program that does the actual printing from T_EX’s device-independent files is responsible for converting from ASCII to a particular font encoding.

T_EX’s internal code also defines the value of constants that begin with a reverse apostrophe; and it provides an index to the `\catcode`, `\mathcode`, `\uccode`, `\lccode`, and `\delcode` tables.

5. Characters of text that have been converted to T_EX’s internal form are said to be of type *ASCII_code*, which is a subrange of the integers.

```
<Types in the outer block 5> ≡
  ASCII_code = 0 .. 255; { eight-bit numbers }
```

This code is used in section 2.

6. The original Pascal compiler was designed in the late 60s, when six-bit character sets were common, so it did not make provision for lowercase letters. Nowadays, of course, we need to deal with both capital and small letters in a convenient way, especially in a program for typesetting; so the present specification of T_EX has been written under the assumption that the Pascal compiler and run-time system permit the use of text files with more than 64 distinguishable characters. More precisely, we assume that the character set contains at least the letters and symbols associated with ASCII codes ‘40 through ‘176; all of these characters are now available on most computer terminals.

Since we are dealing with more characters than were present in the first Pascal compilers, we have to decide what to call the associated data type. Some Pascals use the original name *char* for the characters in text files, even though there now are more than 64 such characters, while other Pascals consider *char* to be a 64-element subrange of a larger data type that has some other name.

In order to accommodate this difference, we shall use the name *text_char* to stand for the data type of the characters that are converted to and from *ASCII_code* when they are input and output. We shall also assume that *text_char* consists of the elements *chr(first_text_char)* through *chr(last_text_char)*, inclusive. The following definitions should be adjusted if necessary.

```
define text_char ≡ char { the data type of characters in text files }
define first_text_char = 0 { ordinal number of the smallest element of text_char }
define last_text_char = 255 { ordinal number of the largest element of text_char }
```

```
<Local variables for initialization 6> ≡
i: integer;
```

This code is used in section 2.

7. The T_EX processor converts between ASCII code and the user’s external character set by means of arrays *xord* and *xchr* that are analogous to Pascal’s *ord* and *chr* functions.

```
<Globals in the outer block 7> ≡
xord: array [text_char] of ASCII_code; { specifies conversion of input characters }
xchr: array [ASCII_code] of text_char; { specifies conversion of output characters }
```

See also sections 12, 13, and 18.

This code is used in section 2.

8. Since we are assuming that our Pascal system is able to read and write the visible characters of standard ASCII (although not necessarily using the ASCII codes to represent them), the following assignment statements initialize the standard part of the *xchr* array properly, without needing any system-dependent changes. On the other hand, it is possible to implement T_EX with less complete character sets, and in such cases it will be necessary to change something here.

```

⟨Set initial values of key variables 8⟩ ≡
  xchr[40] ← '□'; xchr[41] ← '!'; xchr[42] ← '"'; xchr[43] ← '#'; xchr[44] ← '$';
  xchr[45] ← '%'; xchr[46] ← '&'; xchr[47] ← '''';
  xchr[50] ← '('; xchr[51] ← ')'; xchr[52] ← '*'; xchr[53] ← '+'; xchr[54] ← ',';
  xchr[55] ← '-'; xchr[56] ← '.'; xchr[57] ← '/';
  xchr[60] ← '0'; xchr[61] ← '1'; xchr[62] ← '2'; xchr[63] ← '3'; xchr[64] ← '4';
  xchr[65] ← '5'; xchr[66] ← '6'; xchr[67] ← '7';
  xchr[70] ← '8'; xchr[71] ← '9'; xchr[72] ← ':'; xchr[73] ← ';'; xchr[74] ← '<';
  xchr[75] ← '='; xchr[76] ← '>'; xchr[77] ← '?';
  xchr[100] ← '@'; xchr[101] ← 'A'; xchr[102] ← 'B'; xchr[103] ← 'C'; xchr[104] ← 'D';
  xchr[105] ← 'E'; xchr[106] ← 'F'; xchr[107] ← 'G';
  xchr[110] ← 'H'; xchr[111] ← 'I'; xchr[112] ← 'J'; xchr[113] ← 'K'; xchr[114] ← 'L';
  xchr[115] ← 'M'; xchr[116] ← 'N'; xchr[117] ← 'O';
  xchr[120] ← 'P'; xchr[121] ← 'Q'; xchr[122] ← 'R'; xchr[123] ← 'S'; xchr[124] ← 'T';
  xchr[125] ← 'U'; xchr[126] ← 'V'; xchr[127] ← 'W';
  xchr[130] ← 'X'; xchr[131] ← 'Y'; xchr[132] ← 'Z'; xchr[133] ← '['; xchr[134] ← '\';
  xchr[135] ← ']'; xchr[136] ← '^'; xchr[137] ← '_';
  xchr[140] ← '`'; xchr[141] ← 'a'; xchr[142] ← 'b'; xchr[143] ← 'c'; xchr[144] ← 'd';
  xchr[145] ← 'e'; xchr[146] ← 'f'; xchr[147] ← 'g';
  xchr[150] ← 'h'; xchr[151] ← 'i'; xchr[152] ← 'j'; xchr[153] ← 'k'; xchr[154] ← 'l';
  xchr[155] ← 'm'; xchr[156] ← 'n'; xchr[157] ← 'o';
  xchr[160] ← 'p'; xchr[161] ← 'q'; xchr[162] ← 'r'; xchr[163] ← 's'; xchr[164] ← 't';
  xchr[165] ← 'u'; xchr[166] ← 'v'; xchr[167] ← 'w';
  xchr[170] ← 'x'; xchr[171] ← 'y'; xchr[172] ← 'z'; xchr[173] ← '{'; xchr[174] ← '|';
  xchr[175] ← '}'; xchr[176] ← '~';

```

See also sections 10, 11, and 14.

This code is used in section 2.

9. Some of the ASCII codes without visible characters have been given symbolic names in this program because they are used with a special meaning.

```

define null_code = '0' { ASCII code that might disappear }
define carriage_return = '15' { ASCII code used at end of line }
define invalid_code = '177' { ASCII code that many systems prohibit in text files }

```

10. The ASCII code is “standard” only to a certain extent, since many computer installations have found it advantageous to have ready access to more than 94 printing characters. Appendix C of *The T_EXbook* gives a complete specification of the intended correspondence between characters and T_EX’s internal representation.

If T_EX is being used on a garden-variety Pascal for which only standard ASCII codes will appear in the input and output files, it doesn’t really matter what codes are specified in *xchr*[0 .. ’37], but the safest policy is to blank everything out by using the code shown below.

However, other settings of *xchr* will make T_EX more friendly on computers that have an extended character set, so that users can type things like ‘#’ instead of ‘\ne’. People with extended character sets can assign codes arbitrarily, giving an *xchr* equivalent to whatever characters the users of T_EX are allowed to have in their input files. It is best to make the codes correspond to the intended interpretations as shown in Appendix C whenever possible; but this is not necessary. For example, in countries with an alphabet of more than 26 letters, it is usually best to map the additional letters into codes less than ’40. To get the most “permissive” character set, change ‘_’ on the right of these assignment statements to *chr*(*i*).

```
⟨ Set initial values of key variables 8 ⟩ +≡
  for i ← 0 to ’37 do xchr[i] ← ‘_’;
  for i ← ’177 to ’377 do xchr[i] ← ‘_’;
```

11. The following system-independent code makes the *xord* array contain a suitable inverse to the information in *xchr*. Note that if *xchr*[*i*] = *xchr*[*j*] where *i* < *j* < ’177, the value of *xord*[*xchr*[*i*]] will turn out to be *j* or more; hence, standard ASCII code numbers will be used instead of codes below ’40 in case there is a coincidence.

```
⟨ Set initial values of key variables 8 ⟩ +≡
  for i ← first_text_char to last_text_char do xord[chr(i)] ← invalid_code;
  for i ← ’200 to ’377 do xord[xchr[i]] ← i;
  for i ← 0 to ’176 do xord[xchr[i]] ← i;
```

12. String handling. (The following material is copied from the *get_strings_started* procedure of T_EX82, with slight changes.)

```

⟨Globals in the outer block 7⟩ +≡
k, l: 0 .. 255; { small indices or counters }
m, n: text_char; { characters input from pool_file }
s: integer; { number of strings treated so far }

```

13. The global variable *count* keeps track of the total number of characters in strings.

```

⟨Globals in the outer block 7⟩ +≡
count: integer; { how long the string pool is, so far }

```

14. ⟨Set initial values of key variables 8⟩ +≡

```
count ← 0;
```

15. This is the main program, where POOLtype starts and ends.

```

define abort(#) ≡
    begin write_ln(#); goto 9999;
    end

begin initialize;
⟨Make the first 256 strings 16⟩;
s ← 256;
⟨Read the other strings from the POOL file, or give an error message and abort 19⟩;
write_ln(“(”, count : 1, “_characters_in_all.”);
9999: end.

```

16. **define** *lc_hex*(#) ≡ *l* ← #;
if *l* < 10 **then** *l* ← *l* + "0" **else** *l* ← *l* - 10 + "a"

⟨Make the first 256 strings 16⟩ ≡

```

for k ← 0 to 255 do
    begin write(k : 3, “: ”); l ← k;
    if (⟨Character k cannot be printed 17⟩) then
        begin write(xchr["^"], xchr["^"]);
        if k < '100 then l ← k + '100
        else if k < '200 then l ← k - '100
            else begin lc_hex(k div 16); write(xchr[l]); lc_hex(k mod 16); incr(count);
            end;
        count ← count + 2;
    end;
    if l = "" then write(xchr[l], xchr[l])
    else write(xchr[l]);
    incr(count); write_ln(“ ”);
end

```

This code is used in section 15.

17. The first 128 strings will contain 95 standard ASCII characters, and the other 33 characters will be printed in three-symbol form like ‘ \^A ’ unless a system-dependent change is made here. Installations that have an extended character set, where for example $xchr[32] = \text{\#}$, would like string 32 to be the single character 32 instead of the three characters 136 , 136 , 132 (\^Z). On the other hand, even people with an extended character set will want to represent string 15 by \^M , since 15 is *carriage-return*; the idea is to produce visible strings instead of tabs or line-feeds or carriage-returns or bell-rings or characters that are treated anomalously in text files.

Unprintable characters of codes 128–255 are, similarly, rendered \^80 – \^ff .

The boolean expression defined here should be *true* unless T_EX internal code number k corresponds to a non-troublesome visible symbol in the local character set. An appropriate formula for the extended character set recommended in *The T_EXbook* would, for example, be ‘ $k \in [0, 10 \dots 12, 14, 15, 33, 177 \dots 377]$ ’. If character k cannot be printed, and $k < 200$, then character $k + 100$ or $k - 100$ must be printable; moreover, ASCII codes [$41 \dots 46, 60 \dots 71, 136, 141 \dots 146, 160 \dots 171$] must be printable. Thus, at least 80 printable characters are needed.

```
< Character  $k$  cannot be printed 17 > ≡
  ( $k < \text{\^}$ )  $\vee$  ( $k > \text{\^}$ )
```

This code is used in section 16.

18. When the WEB system program called TANGLE processes a source file, it outputs a Pascal program and also a string pool file. The present program reads the latter file, where each string appears as a two-digit decimal length followed by the string itself, and the information is output with its associated index number. The strings are surrounded by double-quote marks; double-quotes in the string itself are repeated.

```
< Globals in the outer block 7 > +≡
```

```
pool_file: packed file of text_char; { the string-pool file output by TANGLE }
xsum: boolean; { has the check sum been found? }
```

19. < Read the other strings from the POOL file, or give an error message and abort 19 > ≡

```
reset(pool_file); xsum ← false;
if eof(pool_file) then abort(‘! I can’t read the POOL file.’);
repeat < Read one string, but abort if there are problems 20 >;
until xsum;
if ¬eof(pool_file) then abort(‘! There’s junk after the check sum’)
```

This code is used in section 15.

```

20. ⟨Read one string, but abort if there are problems 20⟩ ≡
if eof(pool_file) then abort(`!POOL_file_contained_no_checksum`);
read(pool_file, m, n); { read two digits of string }
if m ≠ `*` then
  begin if (xord[m] < "0") ∨ (xord[m] > "9") ∨ (xord[n] < "0") ∨ (xord[n] > "9") then
    abort(`!POOL_line_doesn't_begin_with_two_digits`);
    l ← xord[m] * 10 + xord[n] - "0" * 11; { compute the length }
    write(s : 3, `:_`); count ← count + l;
  for k ← 1 to l do
    begin if eoln(pool_file) then
      begin write_ln(``); abort(`!That_POOL_line_was_too_short`);
      end;
      read(pool_file, m); write(xchr[xord[m]]);
      if xord[m] = "" then write(xchr[""]);
      end;
      write_ln(``); incr(s);
    end
  else xsum ← true;
  read_ln(pool_file)

```

This code is used in section 19.

21. System-dependent changes. This section should be replaced, if necessary, by changes to the program that are necessary to make `POOLtype` work at a particular installation. It is usually best to design your change file so that all changes to previous sections preserve the section numbering; then everybody's version will be consistent with the printed program. More extensive changes, which introduce new sections, can be inserted here; then only the index itself will get a new section number.

22. Index. Indications of system dependencies appear here together with the section numbers where each identifier is used.

abort: [15](#), [19](#), [20](#).

ASCII code: [4](#).

ASCII_code: [5](#), [6](#), [7](#).

boolean: [18](#).

carriage_return: [9](#), [17](#).

char: [6](#).

character set dependencies: [10](#), [17](#).

chr: [6](#), [7](#), [10](#), [11](#).

count: [13](#), [14](#), [15](#), [16](#), [20](#).

decr: [3](#).

do_nothing: [3](#).

eof: [19](#), [20](#).

eobn: [20](#).

false: [19](#).

first_text_char: [6](#), [11](#).

i: [6](#).

incr: [3](#), [16](#), [20](#).

initialize: [2](#), [15](#).

integer: [6](#), [12](#), [13](#).

invalid_code: [9](#), [11](#).

k: [12](#).

l: [12](#).

last_text_char: [6](#), [11](#).

lc_hex: [16](#).

m: [12](#).

n: [12](#).

null_code: [9](#).

ord: [7](#).

output: [2](#).

pool_file: [2](#), [12](#), [18](#), [19](#), [20](#).

POOLtype: [2](#).

read: [20](#).

read_ln: [20](#).

reset: [19](#).

s: [12](#).

system dependencies: [2](#), [6](#), [8](#), [10](#), [17](#), [21](#).

The T_EXbook: [10](#), [17](#).

text_char: [6](#), [7](#), [12](#), [18](#).

true: [17](#), [20](#).

write: [16](#), [20](#).

write_ln: [15](#), [16](#), [20](#).

xchr: [7](#), [8](#), [10](#), [11](#), [16](#), [17](#), [20](#).

xord: [7](#), [11](#), [20](#).

xsum: [18](#), [19](#), [20](#).

- ⟨ Character k cannot be printed 17 ⟩ Used in section 16.
- ⟨ Globals in the outer block 7, 12, 13, 18 ⟩ Used in section 2.
- ⟨ Local variables for initialization 6 ⟩ Used in section 2.
- ⟨ Make the first 256 strings 16 ⟩ Used in section 15.
- ⟨ Read one string, but abort if there are problems 20 ⟩ Used in section 19.
- ⟨ Read the other strings from the POOL file, or give an error message and abort 19 ⟩ Used in section 15.
- ⟨ Set initial values of key variables 8, 10, 11, 14 ⟩ Used in section 2.
- ⟨ Types in the outer block 5 ⟩ Used in section 2.